TECHNICAL DATA

RUST-OLEUM EPOXYSHIELO

EPOXYSHIELD[®] DECORATIVE COLOUR CHIPS

DESCRIPTION ANDUSES

EpoxyShield[®] Decorative Colour Chips are designed for use with EpoxyShield concrete floor coatings. When sprinkled onto a freshly coated surface, these decorative chips bond to the wet film to become a permanent part of the coating. Use on garages, basements, carports, laundry rooms, porches, patios and walkways. EpoxyShield Decorative Colour chips also help to hide dirt and surface imperfections and can be used with water-based or solvent-based concrete coatings.

FEATURES

- Use with EpoxyShield coatings to enhance appearance on concrete floors
- Mix and match chips to customize your colour scheme
- Use additional chips to create a textured finish
- Interior / Exterior durability

PRODUCTS

SKU (1-Pound)	Description
N238469	Blue Gray Blend
N238470	Tan Blend
N238473	Brick Red Blend

INSTRUCTIONS FOR USE

Apply EpoxyShield concrete floor coating (sold separately) in 1.2x1.2m (4'x4') sections. After finishing the first1.2x1.2m (4'x4') section, immediately sprinkle the decorative colour chips onto the freshly coated surface.

IMPORTANT: Apply decorative colour chips to wet paint only. Move on to the next 1.2x1.2m (4'x4') section and continue until complete. Note: Fresh paint can be applied over the loose chips that lay outside the previously painted area. For a high gloss finish, topcoat the colour chipped floor with EpoxyShield Premium Clear Floor Coating.

COVERAGE

Standard Chip Pattern -22.3 m^2 (250 square feet) per bag Heavy Chip Pattern -11.6 m^2 (125 square feet) per bag

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 200 Confederation Parkway Concord, Ontario L4K 4T8

Phone: 800•387•3625 www.rustoleum.ca