



EPOXYSHIELD® ASPHALT POTHOLE FILLER

DESCRIPTION AND USES

EpoxyShield® Asphalt Pothole Filler is a pre-mixed, low odour, ready-to-use "cold Patch" asphalt repair product that permanently patches potholes and large cracks. This environmentally friendly formula remains workable to temperatures as low as 5°C (41°F) and provides excellent adhesion to the asphalt base.

PERFORMANCE CHARACTERISTICS

- Drive-ready immediately
- Use under all weather conditions
- Low odour

PRODUCTS

SKU	Container Size
280607	10 kg
257892	4.5 kg

PRODUCT APPLICATION

SURFACE PREPARATION

The surface must be clean and clear of all contaminants. Clean any loose dirt or dust from the pothole. Square off edges of the pothole to ensure the new material remains in place.

PRODUCT APPLICATION (cont.)

APPLICATION

NOTE: Protective rubber gloves are recommended when using this product.

Place enough Pothole Filler into the hole to fill 5 cm (2") in thickness and tamp well to compact the material. Continue working in 5 cm (2") thick layers until the pothole is filled. Then add an additional 2.5 cm (1") of material above the level of the surrounding asphalt. Compact the material with a hand tamper, roller or by driving over the patch with a car tire until the pothole material is flat to the surrounding driveway. The permanent patch is ready for traffic immediately.

NOTE: For best results, always work in layers of 5 cm (2") thickness and tamp down. Proper tamping between layers is extremely important. To speed hardening and prevent racking, dust with fine sand or Portland cement. In cooler temperatures, keep the product in a warm area for 24 hours prior to use.

COVERAGE

One 10 kg container will cover an area of 0.15 m² (1.65 sq. ft.) to a depth of 2.5 cm (1").

CLEAN UP

Use mineral spirits to clean any tools used or remove material from hands.



TECHNICAL DATA

EPOXYSHIELD® ASPHALT POTHOLE FILLER

PHYSICAL PROPERTIES

		ASPHALT POTHOLE FILLER
Resin Type		Asphalt
Pigment Type		Mineral
Solvents		None
Weight	Per Liter	2.51 kg
	Per Gallon	20.9 lbs.
Solids	By Weight	100%
	By Volume	100%
Volatile Organic Compounds		0 g/l
Practical Coverage (assumes 15% material loss)		Will cover an area of 0.15 m ² (1.65 sq. ft.) to a depth of 2.5 cm (1")
Dry Times at 21-27°C (70-80°F) and 50% Relative Humidity	Drive Ready	Immediately
Shelf Life		1 year
Flash Point		> 93°C (200°F)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.