

ADDITIVE**RUST-OLEUM®****TECHNICAL DATA****CS-45****DURABILITY ADDITIVE****DESCRIPTION AND USES**

The Durability Additive is used to increase the wear resistance of the floor coating. It also decreases the gloss of the coatings which helps hide minor imperfections in the floor.

The Durability Additive is a blend of aluminum oxide and surfactants to ease blending of the additive into the coating.

PRODUCT

280945 Durability Additive

FEATURES

- Increases abrasion resistance by 40%
- Reduces gloss
- Improves hiding power
- Creates a fine micro-texture that increase SCoF
- Particle hardness – 9, Moh's Scale
- Does not affect color of the coating

APPEARANCE

Fine white powder.

RECOMMENDED COATINGS

FastKote

FastKote UV

PACKAGING

Plastic pouch (3lbs)

PRODUCT APPLICATION

After first mixing the coating in accordance to directions, add the entire 3 lbs of Durability Additive to the one gallon of coating and blend for a minimum of 2 minutes to a uniform consistency.

Pour material into a roller pan and apply with a lint free, $\frac{3}{8}$ inch nap roller in accordance to coating recommendations.

Any partial remaining coating in the gallon container should be re-mixed before pouring into the roller pan.

PRODUCT STORAGE

Keep pouch sealed until ready to use. Store out of direct Sunlight at 50-95°F and avoid high moisture.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.