## **TECHNICAL DATA**

**ESH-15** 

RUSFOLEUM EPOXYSHIELO

# EPOXYSHIELD® OIL STAIN REMOVER

## **DESCRIPTION AND USES**

EpoxyShield<sup>®</sup> Oil Stain Remover is formulated to absorb and lift embedded oil stains, as it dries from liquid to powder. It also removes stains from anti-freeze, brake fluid, cooking oils, diesel fluid, grease, hydraulic fluid, power steering fluid, tar, transmission fluid, tree sap and wax.

It is suitable for use on asphalt (blacktop), concrete, composite decks, driveways, garage floors, masonry, patios, walkways, wood and more.

### PRODUCTS

SKU	Description
287584	946 ml Bottle

#### IMPORTANT

# SHAKE VIGOROUSLY FOR 60 SECONDS BEFORE USE.

Do not use on wet surfaces. May cause discoloration on sealed, colored or painted surfaces. Prior use of other cleaners may inhibit performance.

### **PRODUCT APPLICATION**

#### DIRECTIONS

Always test a small area before use. For best results, use above 10°C (50°F), and provide maximum ventilation. Scrape off buildup and sweep area. For exterior applications, apply to the stain, extending one inch beyond perimeter. Allow 5 to 8 hours to dry. Sweep up powder. Immediately rinse the area with a strong stream of water, and allow moisture to evaporate. For interior applications, apply to the stain, extending one inch beyond the perimeter. Allow 8 to 12 hours to dry. Sweep up the powder and immediately rinse with water and allow the moisture to evaporate.

If stain remains, reapply, scrub with stiff- bristled brush, allow to dry for 5 to 8 hours and then sweep up the powder. The rinse the area with water and allow moisture to evaporate.

**CAUTION: EYE AND SKIN IRRITANT.** Provide maximum ventilation during use. Do not mix with other chemicals. Avoid contact with grass or plants. Avoid inhalation of dust when sweeping. Avoid eye and skin contact.

**EYE CONTACT:** Flood eyes repeatedly with water and call physician. **IF SWALLOWED, do not induce vomiting.** Drink a glass of water and call physician immediately.

KEEP OUT OF REACH OF CHILDREN.

## **TECHNICAL DATA**

## **EPOXYSHIELD® OIL STAIN REMOVER**

## PHYSICAL PROPERTIES

	OIL GRABBER
Composition	Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers
Color	White Pourable Emulsion
рН	10-12
VOC	4%
Practical Coverage	946 ml (32 ounces) – 1.7 m² (18 sq ft)
Shelf Life	NA
Flash Point	72°C (162°F)
Caution!	CAUTION: EYE AND SKIN IRRITANT. Provide maximum ventilation during use. Do not mix with other chemicals. Avoid contact with grass or plants. Avoid inhalation of dust when sweeping. Avoid eye and skin contact. EYE CONTACT: Flood eyes repeatedly with water and call physician. IF SWALLOWED, do not induce vomiting. Drink a glass of water and call physician immediately. KEEP OUT OF REACH OF CHILDREN.
Safety Information	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 200 Confederation Parkway Concord, Ontario L4T 4T8

Phone: 800•387•3625 www.rustoleum.ca