

	TECHNICAL DATA	ROC-100
• TRUSTED QUALITY SINCE 1921 • 	RUST-OLEUM® ULTIMATE DRIVEWAY SEALER	

DESCRIPTION AND USES

Rust-Oleum® Ultimate Driveway Sealer is an asphalt-based coating designed to revitalize and protect worn and faded driveways to like-new, jet black appearance.

PERFORMANCE CHARACTERISTICS

- Drive ready in 4 hours
- Easy roller application
- Low odour
- Easy stir formula
- Non tracking formula
- Easy clean-up

PRODUCT

SKU	DESCRIPTION
316552	17- Litre

PRODUCT APPLICATION

SURFACE PREPARATION

To ensure proper adhesion, make sure the entire driveway surface is free of dirt, debris, oil and grease spots. Sweep driveway with a stiff bristle broom. Trim any grass and weeds overgrowing onto the driveway. If grease, oil or chemical stains are present, clean thoroughly with EpoxyShield Spot Cleaner®, remove oil stains with EpoxyShield Oil Stain Remover following package instructions. For general cleaning, apply Krud Kutter, scrub with a stiff bristle broom, then hose off with fresh, clean water. Allow the surface to dry completely before application of sealer.

PRODUCT APPLICATION (cont.)

APPLICATION

Apply only when air, material, and surface temperatures are between 10-32°C (50-90°F) and the relative humidity is below 85% and no rain is forecasted for 48 hours. Surface temperature should not exceed 38°C (100°F). Mix thoroughly to ensure any settled pigment is re-dispersed. Do not dilute. Roll right from the bucket using a 10 mm (3/4") nap roller cover on a 24 cm (9.5") roller frame with the extension handle to apply an even coat. Maintain a wet edge at all times. Cross roll for better coverage. Use a paint brush to trim edges of driveway before applying to the entire surface.

Avoid applying coating in direct sunlight. If pavement is extremely hot, apply a fine water mist prior to coating and brush out any remaining water puddles. To improve uniform coverage on badly worn asphalt, a second coat may be needed. Do not mix or blend this product with any other driveway coating product.

DRY & RECOAT TIMES

Dry times are based on 21°C (70°F). Allow for longer dry times at cooler temperatures. Allow sealer to dry for 1 hour prior to foot traffic and 4 hours prior to vehicle traffic.

COVERAGE

Rust-Oleum Ultimate Driveway Sealer will cover up to 93 m² (1000 sq. ft.) on smooth asphalt. Depending on surface conditions and porosity, previously sealed driveways and applicator's skill, coverage rate may vary.

CLEAN UP

Wash tools and equipment with warm soap and water immediately after use. Use mineral spirits if the product has dried. Properly dispose of all roller covers.

	TECHNICAL DATA	ROC-100
• TRUSTED QUALITY SINCE 1921 • 	RUST-OLEUM® ULTIMATE DRIVEWAY SEALER	

PHYSICAL PROPERTIES

		ULTIMATE DRIVEWAY SEALER
Resin Type		Asphalt
Pigment Type		Mineral
Solvents		Water, Glycol Ether
Weight	Per Liter	1.17 kg
	Per Gallon	9.8 lbs.
Solids	By Weight	50.0%
	By Volume	44.0%
Volatile Organic Compounds		0 g/l
Recommended Dry Film Thickness (DFT) Per Coat		250µ (10.0 mils) depending upon substrate
Wet Film to Achieve DFT (Unthinned Material)		550µ (22.0 mils) depending upon substrate
Practical Coverage at Recommended DFT (assumes 15% material loss)		Will cover up to 93 m ² per 17 Litres (1,000 sq.ft.) (depending upon substrate)
Dry Times at 21-27°C (70-80°F) and 50% Relative Humidity	Foot Traffic	1 hour
	Recoat	1 hour
	Vehicle Traffic	4 hours
	Rain Ready	1 hour
Shelf Life		1 year
Flash Point		> 93°C (200°F)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.