



# KRUD KUTTER® CAULK REMOVER

## DESCRIPTION AND USES

Krud Kutter® Caulk Remover removes most caulks and sealants including silicone, polyurethane, and acrylic caulks and polyurethane foam sealant. The biodegradable gel formula clings and stays wet longer to remove even the toughest sealants, indoors and outdoors. Ideal for sinks, countertops, showers and tubs, baseboards, exterior and interior trim.

## PRODUCT

SKU	DESCRIPTION
381461	710 mL Trigger Sprayer

## APPEARANCE

Colourless to slight yellow, gel-like liquid

## PRODUCT APPLICATION

**IMPORTANT: Test in an inconspicuous area to ensure surface integrity and compatibility.**

### Removing Fresh Caulk:

1. Wipe up as much as possible with rag or towel.
2. Apply Krud Kutter Caulk Remover and wait 1 minute.
3. Wipe up remaining caulk.
4. Rinse surface with a damp rag to finish.

## PRODUCT APPLICATION (cont.)

### Removing Dry Caulk or Sealant:

1. Scrape, cut, or pull away any caulk that can be easily removed and score the edge of remaining caulk.
2. Thoroughly saturate the caulk with Krud Kutter Caulk Remover.
3. Allow to soak for 5-20 minutes or until the caulk loosens (Some applications may require longer soaking depending on the type and amount of caulk to remove).
4. Scrape with a caulk scraper or flexible blade.
5. Repeat application if needed.
6. Wipe surface with a wet, soapy cloth when finished.

FUMES MAY CATCH FIRE. CONTENTS MAY BE HARMFUL. Do not smoke. Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe fumes. Keep out of reach of children. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Wear an organic vapour respirator and safety glasses.

**FIRST AID TREATMENT:** Contains Acetone, Monoethanolamine, 1,3-Dioxolane, Benzyl Alcohol. If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person into fresh air.

## PHYSICAL PROPERTIES

		CAULK REMOVER
<b>Composition</b>		Proprietary blend of low-VOC solvents, biodegradable surfactants and cleaning agents in a water base.
<b>Weight</b>	<b>Per Gallon</b>	8.30 lbs.
	<b>Per Liter</b>	0.99 kg
<b>Color</b>		Colourless to slight yellow
<b>VOC (weight %)</b>		<5
<b>Practical Coverage</b>		Varies with application and substrate
<b>Shelf Life</b>		7 years
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.