

## TECHNICAL DATA

# CABINET TRANSFORMATIONS™ DECORATIVE GLAZE

### DESCRIPTION AND USES

Rust-Oleum® Transformations® Decorative Glaze allows you to add a custom antique finish to any painted surface. This semi-transparent Decorative Glaze has a long open time allowing you to customize your handcrafted, final look. Great for cabinetry, furniture, accessories and more. Ideal for painted wood, laminate, melamine or metal surfaces.

**IMPORTANT:** Apply over a fully cured, painted surface. Test glaze in a small area first before applying on entire project. For more information on this product and to see videos showing different glazing techniques, check us out on YouTube.

### PRODUCTS

#### CABINET TRANSFORMATIONS™

SKU	Description
317936	946 ml Decorative Glaze- Java

### PRODUCT APPLICATION

#### PAINTING CONDITIONS:

Apply when temperature is between 10°C - 35°C (50°F - 95°F) and the relative humidity is below 70%. Preparation: The Decorative Glaze must be applied over a clean, fully cured surface. For best results, apply over a non-glossy finish. In order to get a high-end finish look, a cloth such as Cheesecloth or a lint-free rag or Tack Cloth should be used to remove portions of the Decorative Glaze. To complete your project, use a water-based Varathane Clear Finish to seal in the Decorative Glaze finish.

#### PAINTING:

Stir thoroughly. Using a 50 mm (2") synthetic or foam brush, coat the surface with the Decorative Glaze. Be certain to get the Decorative Glaze in all corners, crevices, and raised panel sections.

#### TIP:

A cotton swab or artist's brush is very handy! Using Cheesecloth, wipe the surface (using varying pressure) in the direction of the grain or brush marks to remove the Decorative Glaze to desired look. If not satisfied with the appearance of Decorative Glaze, while wet wipe the surface down completely with a clean, damp rag and repeat the glazing process. Let dry a minimum of 8 hours and finish by applying a Varathane Clear Finish to seal in the Decorative Glaze finish.

#### DRY TIME:

Let dry a minimum of 8 hours before applying a Varathane Clear Finish.

#### CLEAN UP:

Clean brush and other tools with soap and water.

#### COVERAGE:

1.86 m<sup>2</sup> (200 ft<sup>2</sup>).

### REGULATORY

**CAUTION:** Use only in a well ventilated area. Do not breathe vapours. May irritate eyes and skin. Do not get in eyes, on skin or clothing.

KEEP OUT OF REACH OF CHILDREN.

**FIRST AID TREATMENT:** If breathed in, move person to fresh air. If swallowed call Poison Control Centre or doctor immediately. Do not induce vomiting. If on skin, rinse well with water.

## TECHNICAL DATA

### CABINET TRANSFORMATIONS™ DECORATIVE GLAZE

#### PHYSICAL PROPERTIES

		DECORATIVE GLAZE
Resin Type		Acrylic
Pigment Type		None
Solvents		Propylene Glycol
Weight	Per Gallon	2.10 lbs.
	Per Liter	1.04 kg
Volatile Organic Compounds		856 g/l (7.12 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		NA
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Allow Bond Coat to Dry	2 hours
	Allow Decorative Glaze to Dry	8 hours
Shelf Life		3 years
Flash Point		>93°C (>200°F)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.