

MOLDEX® POWER OUTDOOR CLEANER

DESCRIPTION AND USES

Moldex® POWER! contains unique properties that remove tough stains caused by algae, mould and mildew leaving surfaces completely clean.

When mixed (1:10) with water, one bottle of concentrate makes 41.6 L (11 gallons) of premix, and cleans up to 186 m² (2000 sq. ft.) (less on rougher surfaces), and can be applied by pressure washer, pump-up sprayer, brush or roller. Contains anti-corrosive agents to safeguard pressure washer parts (bleach can erode O-rings).

Recommended For: Exterior siding (wood, vinyl, aluminum), roofing of all types (asphalt shingles, fibreglass shingles, cedar, tile), gutters, stucco, brick and cement blocks, masonry, walkways and walls.

PERFORMANCE CHARACTERISTICS

- · Removes stains from mould, mildew and algae
- Removes dirt and grime
- Non-Bleach formula
- Can be used near plants and shrubs

PRODUCT

SKU	DESCRIPTION	
4140	3.78 L Bottle	

PRODUCT APPLICATION

IMPORTANT: Read entire label before use.

When using a pressure washer to clean painted surfaces, please be aware that water pressure alone may remove paint, or highlight existing discolouration caused by the sun's UV rays.

PREPARATION

Always test on an inconspicuous area first. With a garden hose, rinse any nearby plants with clean water. Any overspray can be neutralized with large volumes of water.

DIRECTIONS

Manual Use: Wear appropriate protective apparel when handling concentrate (face protection, rubber gloves, and/or apron).

- 1. Mix at 1:10 parts concentrate with water.
- 2. Fill spray bottles, buckets, or pump sprayers and spray to wet the area to be cleaned. Work in manageable sections if cleaning a large area.
- Wait several minutes to allow cleaner to work before wiping, scrubbing or mopping the surface clean.
- Rinse with clean water, allow surfaces to dry before resuming use or traffic.

PRODUCT APPLICATION (cont.)

Pressure Washer Use:

- Rinse surrounding plants with water, before and after application.
- Wet surface to be cleaned, prior to applying the product.
- Place detergent application siphon tube and screen filter directly into container. Open meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer
- **4.** Spray at low pressure onto a wet surface.
- On vertical surfaces, always spray from the top down.
- Allow product to remain on the surface for 3 to 5 minutes to penetrate. Do not allow product to dry on surface.
- Remove siphon tube from solution and rinse surface with high pressure water spray thoroughly.
- 8. Flush siphon tube with clean water prior to storage.

On extremely soiled or mildewed surfaces it may be necessary to scrub with a bristle brush, and a second application may be needed. Mildew stains may not be completely removed from porous surfaces. In case of severe oil and grease stains on porous surfaces, oil may bleed to the surface or leave a residual stain. Repeat applications may lighten stains, but not remove completely.

STORAGE

Store in original container in area inaccessible to children and pets. Store in cool, dry area. Non-refillable container. Do not reuse or refill. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

DISPOSAL

To dispose of empty containers and unused product, contact your local environmental regulatory agency.

REGULATORY

CAUTION: MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not mix with other chemicals. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Keep out of reach of children. FIRST AID TREATMENT: Contains: Sodium metasilicate, Lauryldimethylamine oxide. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

KEEP OUT OF REACH OF CHILDREN.

Form: ARJ-2345 Rev.: 012422



MOLDEX® POWER OUTDOOR CLEANER

PHYSICAL PROPERTIES

		POWER OUTDOOR CLEANER	
Composition		Proprietary Blend	
рН		12-13	
Weight	Per Gallon	8.43 lbs	
	Per Liter	1.01 kg	
Solids	By Weight	2.84%	
	By Volume	1.67%	
Volatile Organic Compounds		524 g/l	
Odor		Mild	
Practical Coverage		Cleans up to 186 m ² (2000 sq. ft.) per 3.78 L (1 gallon) of concentrate	
Shelf Life		2 Years	
Flash Point		> 94°C (200°F)	
Caution		KEEP OUT OF REACH OF CHILDREN.	
Safety Information		For Additional Information, See SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 800·387·3625 www.rustoleum.ca

Form: ARJ-2345 Rev.: 012422