

# KRUD KUTTER® STICKY KRUD ADHESIVE REMOVER

# **DESCRIPTION AND USES**

Krud Kutter<sup>®</sup> Sticky Krud Adhesive Remover is designed to quickly remove residue left from stickers, labels and gluey material. Also removes asphalt, blacktop, carbon black, caulk, diesel soot, duct tape, foam, fresh oil-based paint and stain, liquid insulation, liquid nails, mastic, road & roofing tar, silicone sealant, water seal and more.

Krud Kutter Sticky Krud Adhesive Remover is effective on most surfaces. Not recommended on varnish, suede, leather, silk, rubber or elastic items.

**IMPORTANT:** Always test first on an inconspicuous area.

#### PRODUCT

SKU	DESCRIPTION	
304971	355mL Trigger Sprayer	

## PRODUCT APPLICATION

### **DIRECTIONS - WET SURFACE**

Using a disposable cotton towel, remove as much wet solution as possible. Apply remover and allow to penetrate for 2-5 minutes. Peel, scrape or wipe. Rinse.

#### **DIRECTIONS - DRY SURFACE**

To dispose of empty containers and unused product, contact your local environmental regulatory agency.

## REGULATORY

CONTENTS MAY BE HARMFUL. Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe fumes. Keep out of reach of children. Use only in a well-ventilated area. Keep away from flames or sparks. Wear an organic vapour respirator and safety glasses. FIRST AID TREATMENT: Contains hydrotreated light distillate, d-limonene, dipropylene glycol mono methyl ether and dimethyl-2-methyl glutarate. If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person into fresh air.

## KEEP OUT OF REACH OF CHILDREN.

PHYSICAL PROPERTIES		
	STICKY KRUD ADHESIVE REMOVER	
Composition	D-Limonene Terpene, Dipropylene Glycol Mono Methyl Ether	
pH	3.5	
VOC	Consumer Weight Percent - 10%	
Shelf Life	NA	
Flash Point	78°C (172°F)	
Warning!	KEEP OUT OF REACH OF CHILDREN.	
Safety Information	For additional information, see SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 800-387-3625 www.rustoleum.ca

Form: ARJ-2452 Rev.: 080222